



Model No: HW0021-1

System	System Security	Supports three-level account, password, user authority management.
	OS	Embedded Linux OS
	Processor	Hi3518EV200
	P2P (Free)	No need to preset camera, Offer free P2P(ZZZZ-xxxx-xxxx), Plug&play, Support QR code scanning to view
	Onvif Protocol	Support ONVIF2.1 Protocol
	Multi-device function	Support 12 language remote surveillance, record, alarm, wifi setting etc.
	PC client	Support remote multi-devices monitor, record, alarm etc;Support windows and mac os
	Cell Phone View	Self R&D APP, Support Iphone,Android smart Phone
	TF Card Record	Support Max 128G TF card .Support the scheduled record,scheduled snapshot,Support Intelligent record playback via browser
Lens	Lens Type	Lens Standard : 3.6 mm
	IR-CUT	Build-in IR CUT, no color cast,auto switch when IR on
Video	Image Compression	H.264/MJPEG
	Sensor	1/4 Cmos 1MP
	Video Parameters	Brightness, Contrast,Saturation,Exposure,sharpness,VerticalAnd Horizontal can be adjusted
	Image Frame Rate	50Hz:25fps/60HZ:30fps (1280×720)
	First Stream	720P-(1280x720),(640x352)
	Second Stream	VGA-(640x352),(320x176)
Audio	Compression format	G.726/G.711 (G.711 Default)
	Audio In	Built in Mic,also external supported
	Audio Out	Built in Speaker,also external supported
Night Vision	Night Visibility	6 Φ5 IR LEDs, Night visibility up to 15 meters
	LUX	0 LUX
Pan/Tilt	Preset	Support 8 Preset Positions
	Rotation Angle	Pan:355°, Tilt: 90°
	Rotation Speed	Pan: Speed Range 5-30°/ S; Tilt: Speed Range 5-50°/ S;
Alarm	Motion Detect	Support 4 Independent detection areas(Sensitivity can be adjustd 1-100)
	Alarm Action	Support Email Photo Alert,Snapshot and Record uploaded to FTP or TF Card
Network	Ethernet Interface	One 10/100Mbps RJ-45
	Supported Protocol	TCP/IP, HTTP, TCP, ICMP, UDP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP etc.
	Access agreement	Support ONVIF2.1 Protocol
	IP Mode	Dynamic IP address, static IP address, PPPOE
	Online Visitor	Support Max 6 visitors at the same time (First Stream:3 visitors;Second Stream:3 visitors)
	Supported OS	Support Microsoft Win XP/Win7/Win8/ win10/Mac OS.
	Browser	Support Internet Explorer8-11 ,FireFox,Google Browser, etc
	One key setting	Support one key setting function connect WIFI
	Wireless Standard	WIFI, 802.11b/g/n
Others	OSD	Support the OSD name, date and time info superposition (Open/Off)
	Product Type	Cartoon Robot/ Indoor use
	Color	White;
	Power	DC5V 1A
	Working Temperature	-10~50 °C
	Working Humidity	95% RH
	Size	Item: 112 x 102.6mm (HxW); Packaging: 182 x 110 x 149mm (LxWxH)
	Weight	N.W.: 280g G.W.: 600g(Note:Actual Weight Final)
	Accessories	Adaptor, CD,User manual,Bracket,Screws,Ethernet Cable
	Certification	CE,FCC,RoHS
Warranty	Limited 2-Year Warranty	