



Model: HW0029-5

System	System Security	Supports three-level account, password, user authority management.
	OS	Embedded Linux OS
	Processor	Hi3516C+IMX291 Star light sensor
	P2P(Free)	No need to preset camera, Offer free P2P, Plug&play, Support QR code scanning to view
	Onvif Protocol	Support ONVIF protocol
	PC Browser	Support 12 language remote surveillance, record, alarm, wifi setting etc.
	PC client	Support remote multi-devices monitor, record, alarm etc.
	Cell Phone View	Self R&D APP, Support Iphone,Android smart Phone
	TF Card Record	Built In 16G TF Card,support max 128G
Lens	Lens type	Lens Standard : 6mm
	IR-CUT	Build-in IR CUT, No color cast
Solar Power	Material	Efficient thin-film solar panels
	Battery	Standby time is 54 hours when it is with the full batteries
Video	Image Compression	H.264 Main profile/Baseline profile
	Sensor	1/2.8 2M Starlight CMOS Sensor
	Video Parameters	Brightness, Contrast,Saturation,Exposure,sharpness can be adjusted
	Image Frame Rate	50Hz:25fps/60HZ:30fps (1920×1080)
	Stream	First Stream: 1080P- (1920×1080) (1280×720) 、 (640×352) Second Stream: 1280×960,1280×720 VGA-(640×352) 、 (320×176)
Night Vision	Night Visibility	100 Meters
	Lux	0.0001LUX(Starlight Level)
Pan/Tilt	Preset	None
	Rotation Angle	None
	Rotation Speed	None
Alarm	Motion Detect	Support 4 Independent detection areas(Sensitivity can be adjustd 1-100)
	Alarm Action	Support Email Photo Alert,Snapshot and Record saved to TF Card

Network	Ethernet Interface	One 10/100Mbps RJ-45
	Supported Protocol	TCP/IP, HTTP, TCP, ICMP, UDP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP etc
	Access Protocol	Support Onvif protocol
	Online Visitor	Support Max 6 visitors at the same time (First Stream:3 visitors;Second Stream:3 visitors)
	IP Mode	Dynamic IP address, static IP address, PPPOE
	Supported OS	Microsoft Win98 SE/ME/2000/XP/Win7/Win8/ Mac OS.
	Browser	IE6.0, IE7.0, IE8.0, FireFox, Google or other standard browser
	AP Function	Support AP connect WIFI
	Wireless Standard	WIFI,802.11 b/g/n
Others	OSD	Support the OSD name, date and time info superposition (On/Off)
	Product Type	Metal Bullet, Outdoor waterproof
	Power	DC5V/2A
	Solar Power	Support Solar Power and Battery (24AH)
	Battery Material	Lithium
	Battery Capacity	2x12AH
	Color	Silver
	Working Temperature	-10~70℃
	Working Humidity	95% RH
	Size	Item: 370*286*96mm (LxWxH) Packaging: 430x330x130mm (LxWxH)
	Weight	N.W.: 2880g G.W.:4320g (Note:Actual Weight Final)
	Accessories	Adaptor, WIFI Antenna, CD (including User manual), Bracket, Screw
Certification	Certification	CE, FCC, RoHS
Warranty	Warranty	Two years