



### Model: HW0029-6

<b>System</b>	<b>System Security</b>	Supports three-level account, password, user authority management.
	<b>OS</b>	Embedded Linux OS
	<b>Processor</b>	Hi3516C+IMX291 Star light sensor
	<b>P2P(Free)</b>	No need to preset camera, Offer free P2P(ZZZZ-000xxx-xxxxx), Plug&play, Support QR code scanning to view
	<b>Onvif Protocol</b>	Support ONVIF protocol
	<b>PC Browser</b>	Support 12 language remote surveillance, record, alarm, wifi setting etc.
	<b>PC client</b>	Support remote multi-devices monitor, record, alarm etc.
	<b>Cell Phone View</b>	Self R&D APP, Support Iphone,Android smart Phone
	<b>TF Card Record</b>	Built In 16G TF Card,support max 128G
<b>Lens</b>	<b>Lens type</b>	Lens Standard : 6 mm
	<b>IR-CUT</b>	Build-in IR CUT, No color cast
<b>Solar Power</b>	<b>Material</b>	Efficient thin-film solar panels
	<b>Battery</b>	Standby time is 40 hours when it is with the full batteries
<b>Video</b>	<b>Image Compression</b>	H.264 Main profile/Baseline profile
	<b>Sensor</b>	1/2.8 2M Starlight CMOS Sensor
	<b>Video Parameters</b>	Brightness, Contrast,Saturation,Exposure,sharpness can be adjusted
	<b>Image Frame Rate</b>	50Hz:25fps/60HZ:30fps (1920×1080)
	<b>Stream</b>	First Stream: 1080P- (1920×1080) (1280x720) 、 ( 640x352 ) Second Stream: 1280×960,1280×720 VGA-(640x352) 、 ( 320x176)
<b>Night Vision</b>	<b>Night Visibility</b>	100 Meters
	<b>Lux</b>	0.0001LUX(Starlight Level)
<b>Alarm</b>	<b>Motion Detect</b>	Support 4 Independent detection areas(Sensitivity can be adjustd 1-100)
	<b>Alarm Action</b>	Support Email Photo Alert,Snapshot and Record saved to TF Card
<b>SIM</b>	<b>TD-SCDMA</b>	Support 4G (B38/B39/B40/B41) , 3G ( B34/B39) , 2G (900/1800MHZ)
	<b>WCDMA</b>	Support 4G (B1/B3/B5) , 3G (B1) , 2G (900/1800MHZ)
	<b>CDMA2000</b>	Support 4G (B1/B3/B5)

<b>WIFI</b>	<b>Wifi</b>	WIFI, 802.11 b/g/n
	<b>WIFI Frequency</b>	2400~2483.5MHZ
	<b>WIFI Security</b>	WEP, WPA-PSK, WPA2-PSK, WPA-WPA2 mixed
	<b>WIFI Users</b>	Max support 9 users
<b>Network</b>	<b>Ethernet Interface</b>	One 10/100Mbps RJ-45
	<b>Supported Protocol</b>	TCP/IP, HTTP, TCP, ICMP, UDP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP etc
	<b>Access Protocol</b>	Support Onvif protocol
	<b>Online Visitor</b>	Support Max 6 visitors at the same time(First Stream:3 visitors;Second Stream:3 visitors)
	<b>IP Mode</b>	Dynamic IP address, static IP address, PPPOE
	<b>Supported OS</b>	Microsoft Win98 SE/ME/2000/XP/Win7/Win8/ Mac OS.
	<b>Browser</b>	IE6.0, IE7.0, IE8.0, FireFox, Google or other standard browser
	<b>AP Function</b>	Support AP connect WIFI
<b>Others</b>	<b>OSD</b>	Support the OSD name, date and time info superposition (On/Off)
	<b>Product Type</b>	Metal Bullet, Outdoor waterproof
	<b>Power</b>	DC5V/2A
	<b>Solar Power</b>	Support Solar Power and Battery (24AH)
	<b>Battery Material</b>	Lithium
	<b>Battery Capacity</b>	2x12AH
	<b>Color</b>	Silver
	<b>Working Temperature</b>	-10~70℃
	<b>Working Humidity</b>	95% RH
	<b>Size</b>	Item: 370*286*96 mm (LxWxH); Packaging:430x330x130mm(LxWxH)
	<b>Weight</b>	N.W.: 2960g G.W. : 4400g (Note:Actual Weight Final)
	<b>Accessories</b>	Adaptor, WIFI Antenna*3, CD (including User manual), Bracket, Screw
<b>Certification</b>	<b>Certification</b>	CE, FCC, RoHS
<b>Warranty</b>	<b>Warranty</b>	Two years